



Range of application:

Balances loads up to 2500 kg in difficult-to-access areas (façade apertures, roof overhangs).

Description:

- cable remote control operated, motor-driven counterweights to balance loads up to 2500 kg
- integrated "Release" safety function for usage with vacuum lifting devices (have to be equipped accordingly)
- powered by a high capacity rechargeable battery
- integrated gauge for monitoring power supply
- Counterweights: 30 pcs. removable (1 counterweight = 25kg)
- Overhang: adjustable for different loads
- 150 m = 2500 kg
- 175 m = 2000 kg
- 200 m = 1500 kg
- 250 m = 1000 kg
- 300 m = 700 kg
- Total length: 6 m
- Controls: cable remote control
- Power supply: 24 V battery

Schutzvermerk ISO 16016 beachten		(Zul. Abw.) DIN ISO 2768-m	(Oberfläche) DIN EN ISO 1302	Maßstab _	(Gewicht) 1392,8 kg
				(Werkstoff, Halbzeug)	
				(Benennung)	
				GGA 2500 30/3,0/6,0 mVH-e	
				(Zeichnungsnummer)	
				EG_1011186	
				Blatt	
				1	
				1 BL	
Zust.	Änderung	Datum	Name (Urspr.)	(Ers. f.)	(Ers. d.)

